

**CAMRECORD-SPRINTER SERIES** 

# Sprinter-HD

High-Speed Video Camera



- ☑ TROUBLESHOOTING
- ✓ RESEARCH
- ✓ SCIENTIFIC
- 3.500 fps with 1280 x 860 pixels
- Standalone operation
- SSD backup storage up to 1TB
- Fast 16 GB camera memory
- TimeViewer user software included

# Sprinter-HD High-Speed Video Camera



# **DESCRIPTION**

Sprinter-HD of the CamRecord-Sprinter series is a high-speed camera with integrated frame memory. Various trigger and synchronization features makes the camera an ideal tool for research and industrial applications. The camera is controlled by TimeViewer software via GigE interface.

#### PERFORMANCE (EXAMPLES)

time

# **INTERFACES**

Trigger input (TI)	TTL, 3.3 - 5 V, optically isolated, recording of sequence
Synchronisation input (SI)	TTL, 3.3 - 5 V, optically isolated, frame synchronization
Synchronisation output (TO)	TTL, 2.0 - 4.0 V, optically isolated, frame synchronous output signal
Programmable output (PO)	reserved
GigE	control and download

# **MODELS**

Sprinter-HD-M	monochrome Camera
Sprinter-HD-C	color Camera


#### **SPECIFICATIONS**


01 2011 1071110110	
Sensor resolution	1280×860
Frame rate @ max. sensor res.	3.504 fps
Memory	16 GB internal
Image sensor	CMOS, Global Shutter
Exposure time	2 µs - 1/framerate
Active area	17.5 mm x 11.8 mm
Sensor diagonal dimension	21.1 mm
Pixel size	13.7 µm
A/D conversion	8 Bit
Dynamic	48 dB
Sensitivity	25 V/lux × s @ 525 nm
Trigger modes	internal free-run, switch, rising or falling edge, pre- and post-trigger
Power	12 VDC
Weight	1400 g without mount
Dimensions	150 mm x 92 mm x 92 mm
Housing	lightweight anodised aluminium
SSD harddrive bay	data storage and backup
PC software	TimeViewer for Windows (support for version 7, 8 and 10) for capture, video playback, export, image analysis with object tracking
Scope of delivery	Camera with 256 GB SSD, TimeViewer, Power supply, GigE- cable and manual


# **ACCESSORIES**


CR-FM	F-Mount lens adapter
CR-FMG	F-Mount lens adapter with aperture control
CR-CM	C-Mount lens adapter

# **TECHNICAL DRAWING**









# **CONTACT INFORMATION**

 Optronis GmbH
 Phone: +49 7851 91 26 - 0

 Ludwigstraße 2
 Fax: +49 7851 91 26 - 10

 77694 Kehl
 info@optronis.com

 Germany
 www.optronis.com

The information given herein is believed to be reliable, however Optronis makes no warranties as to its accuracy or completeness. Data sheet is subject to modifications at any time. Ver. C

